



D	200/M56x4-St/St	78	26	-	200	-	-	-	M56x4	85	46	194kN (19400kg)	
	150/M56x4-St/St	78	26	-	150	-	-	-	M56x4	85	46	194kN (19400kg)	
	100/M56x4-St/St	78	26	-	100	-	-	-	M56x4	85	46	153kN (15300kg)	
	200/M48x3-St/St	66	26	-	200	-	-	-	M48x3	75	41	144kN (14400kg)	
	150/M48x3-St/St	66	26	-	150	-	-	-	M48x3	75	41	144kN (14400kg)	
	100/M48x3-St/St	66	26	-	100	-	-	-	M48x3	75	41	144kN (14400kg)	
	200/M42x3-St/St	60	26	-	200	-	-	-	M42x3	65	36	105kN (10500kg)	
	150/M42x3-St/St	60	26	-	150	-	-	-	M42x3	65	36	105kN (10500kg)	
	100/M42x3-St/St	60	26	-	100	-	-	-	M42x3	65	36	105kN (10500kg)	
E	200/M36x3-St/St	55	23	-	200	-	-	-	M36x3	55	30	72kN (7200kg)	
	150/M36x3-St/St	55	23	-	150	-	-	-	M36x3	55	30	72kN (7200kg)	
	100/M36x3-St/St	55	23	-	100	-	-	-	M36x3	55	30	72kN (7200kg)	
	80/M36x3-St/St	55	23	-	80	-	-	-	M36x3	55	30	72kN (7200kg)	
	60/M36x3-St/St	55	23	-	60	-	-	-	M36x3	55	30	53kN (5300kg)	
	200/M30x2-St/St	50	23	-	200	-	-	-	M30x2	46	24	49kN (4900kg)	
	150/M30x2-St/St	50	23	-	150	-	-	-	M30x2	46	24	49kN (4900kg)	
	100/M30x2-St/St	50	23	-	100	-	-	-	M30x2	46	24	49kN (4900kg)	
	80/M30x2-St/St	50	23	-	80	-	-	-	M30x2	46	24	49kN (4900kg)	
F	60/M30x2-St/St	50	23	-	60	-	-	-	M30x2	46	24	49kN (4900kg)	
	200/M24x2-St/St	45	23	-	200	-	-	-	M24x2	36	19	26kN (2600kg)	
	150/M24x2-St/St	45	23	-	150	-	-	-	M24x2	36	19	26kN (2600kg)	
	100/M24x2-St/St	45	23	-	100	-	-	-	M24x2	36	19	26kN (2600kg)	
	80/M24x2-St/St	45	23	-	80	-	-	-	M24x2	36	19	26kN (2600kg)	
	60/M24x2-St/St	45	23	-	60	-	-	-	M24x2	36	19	26kN (2600kg)	
	OZNAČENÍ	A	B	C	D	E	F	G	M	S1	S2	cena	doporučené max. zatížení F [N] (kg)

NOHA STAVITELNÁ - VÝKYVNÁ M24-M56, OCELOVÁ

ocel nerezová

KLÍČ S1
ocel nerezová

ocel nerezová

A min

B

ϕD

KLÍČ S2

max $\pm 1.5^\circ$

152

170

D	200/M56x4-VA/VA	78	26	-	200	-	-	-	M56x4	85	46	292kN (29200kg)	
	150/M56x4-VA/VA	78	26	-	150	-	-	-	M56x4	85	46	292kN (29200kg)	
	100/M56x4-VA/VA	78	26	-	100	-	-	-	M56x4	85	46	153kN (15300kg)	
	200/M48x3-VA/VA	66	26	-	200	-	-	-	M48x3	75	41	216kN (21600kg)	
	150/M48x3-VA/VA	66	26	-	150	-	-	-	M48x3	75	41	216kN (21600kg)	
	100/M48x3-VA/VA	66	26	-	100	-	-	-	M48x3	75	41	153kN (15300kg)	
	200/M42x3-VA/VA	60	26	-	200	-	-	-	M42x3	65	36	158kN (15800kg)	
	150/M42x3-VA/VA	60	26	-	150	-	-	-	M42x3	65	36	158kN (15800kg)	
	100/M42x3-VA/VA	60	26	-	100	-	-	-	M42x3	65	36	153kN (15300kg)	
E	200/M36x3-VA/VA	55	23	-	200	-	-	-	M36x3	55	30	108kN (10800kg)	
	150/M36x3-VA/VA	55	23	-	150	-	-	-	M36x3	55	30	108kN (10800kg)	
	100/M36x3-VA/VA	55	23	-	100	-	-	-	M36x3	55	30	108kN (10800kg)	
	80/M36x3-VA/VA	55	23	-	80	-	-	-	M36x3	55	30	97kN (9700kg)	
	60/M36x3-VA/VA	55	23	-	60	-	-	-	M36x3	55	30	53kN (5300kg)	
	200/M30x2-VA/VA	50	23	-	200	-	-	-	M30x2	46	24	74,5kN (7450kg)	
	150/M30x2-VA/VA	50	23	-	150	-	-	-	M30x2	46	24	74,5kN (7450kg)	
	100/M30x2-VA/VA	50	23	-	100	-	-	-	M30x2	46	24	74,5kN (7450kg)	
	80/M30x2-VA/VA	50	23	-	80	-	-	-	M30x2	46	24	74,5kN (7450kg)	
F	60/M30x2-VA/VA	50	23	-	60	-	-	-	M30x2	46	24	53kN (5300kg)	
	200/M24x2-VA/VA	45	23	-	200	-	-	-	M24x2	36	19	40kN (4000kg)	
	150/M24x2-VA/VA	45	23	-	150	-	-	-	M24x2	36	19	40kN (4000kg)	
	100/M24x2-VA/VA	45	23	-	100	-	-	-	M24x2	36	19	40kN (4000kg)	
	80/M24x2-VA/VA	45	23	-	80	-	-	-	M24x2	36	19	40kN (4000kg)	
	60/M24x2-VA/VA	45	23	-	60	-	-	-	M24x2	36	19	40kN (4000kg)	
	OZNAČENÍ	A	B	C	D	E	F	G	M	S1	S2	cena	doporučené max. zatížení F [N] (kg)

NOHA STAVITELNÁ - VÝKYVNÁ M24-M56, NEREZOVÁ